

Tecumseh - Hermetique Condensing Units



R404a Low Temperature

Model	Displ (cc)	HP	Motor Type	FLA	Capacity @ -23.3C (W)	Suction : Liquid	Dimensions (mm)			No. of Fan/ Diameter (mm)	Weight (kg)
							L	W	H		
AET2425ZBR	12	5/8	CSR	4.8	609	3/8 : 1/4	495	350	300	1/300	24
CAJT2428ZBR	15.2	1/2	CSIR	4.0	720	1/2 : 1/4	485	430	340	1/300	34
CAJT2432ZBR	18.3	5/8	CSR	3.1	882	1/2 : 1/4	485	430	340	1/300	34
CAJT2446ZBR	26.2	3/4	CSR	4.0	1291	1/2 : 3/8	485	430	340	1/300	36
CAJT2464ZBR	34.4	1 1/2	CSR	5.6	1704	5/8 : 3/8	610	510	445	1/350	44
TAJT2464ZBR	34.4	1 1/2	3	2.3							
FHT2480ZBR	53.2	2	CSR	8.3	2432	5/8 : 3/8	630	510	445	1/350	57
TFHT2480ZBR	53.2	2	3	2.8							
FHT2511ZBR	74.3	2 1/2	CSR	12.1	3274	5/8 : 3/8	1002	618	469	2/350	54
TFHT2511ZBR	74.3	2 1/2	3	4.0							
TAGT2516ZBR	112.5	4	3	5.2	4519	7/8 : 3/8	1020	593	465	2/350	107
TAGT2522ZBR	134.8	5 1/2	3	6.7	5826	1 1/8 : 3/8	1080	650	565	2/400	107

R404a Medium Temperature

Model	Displ (cc)	HP	Motor Type	FLA	Capacity @ -5C (W)	Suction : Liquid	Dimensions (mm)			No. of Fan/ Diameter (mm)	Weight (kg)
							L	W	H		
AET4430ZHR	5.7	1/4	CSIR	2.2	525	3/8 : 1/4	404	322	257	1/250	25
AET4440ZHR	7.6	1/3	CSR	2.5	693	3/8 : 1/4	501	336	298	1/250	28
AET4450ZHR	9.4	3/8	CSR	3.1	981	3/8 : 1/4	501	336	298	1/300	29
AET4460ZHR	11.3	1/2	CSR	3.9	1142	3/8 : 1/4	501	336	298	1/300	29
AET4470ZHR	12.2	1/2	CSR	4.5	1315	3/8 : 1/4	496	433	338	1/300	30
CAJT9480ZHR	15.2	5/8	CSR	4.5	1495	1/2 : 3/8	495	430	340	1/300	41
CAJT9510ZHR	18.3	1	CSR	5.5	1868	5/8 : 3/8	610	510	395	1/350	43
CAJT9513ZHR	24.2	1 1/8	CSR	6.9	2426	5/8 : 3/8	630	510	445	1/350	45
CAJT4517ZHR	26	1 1/4	CSR	7.6	2643	5/8 : 3/8	630	510	445	1/350	51
TAJT4517ZHR	26	1 1/4	3ø	3.1							
CAJT4519ZHR	34.5	1 1/2	CSR	10.4	3526	5/8 : 3/8	600	600	558	1/400	72
TAJT4519ZHR	34.5	1 1/2	3ø	4.5							
FHT4524ZHR	43.5	2	CSR	11.0	4012	5/8 : 3/8	608	600	558	1/400	73
TFHT4524ZHR	43.5	2	3ø	4.2							
FHT4531ZHR	56.7	2 1/2	CSR	14.8	5462	7/8 : 1/2	642	1002	469	2/350	80
THFT4531ZHR	56.7	2 1/2	3ø	5.4							
FHT4540ZHR	74.3	3	CSR	20.8	6517	7/8 : 1/2	650	1080	565	2/400	90
TFHT4540ZHR	74.3	3	3ø	7.0							
TAGT4546ZHR	90.2	4	3ø	7.5	6352	7/8 : 5/8	644	1080	565	2/400	98
TAGT4553ZHR	100.7	4 1/2	3ø	7.8	8359	7/8 : 5/8	644	1080	565	2/400	98
TAGT4561ZHR	112.5	5	3ø	10.0	8691	1 1/8 : 5/8	644	1080	565	2/400	106
TAGT4568ZHR	124.4	6	3ø	10.2	10928	1 1/8 : 5/8	650	1080	565	2/400	135
TAGT4573ZHR	134.8	6 1/2	3ø	10.9	11200	1 1/8 : 5/8	650	1080	565	2/400	135

R134a Medium Temperature

Model	Displ (cc)	HP	Motor Type	FLA	Capacity @ -5C (W)	Suction : Liquid	Dimensions (mm)			No. of Fan/ Diameter (mm)	Weight (kg)
							L	W	H		
AET4425YHR	6.7	1/5	CSIR	1.9	402	3/8 : 1/4	397	312	225	1/200	17
AET4430YHR	8	1/4	CSIR	2.6	510	3/8 : 1/4	400	319	257	1/200	18
AET4440YHR	10.3	3/8	CSIR	3.1	656	3/8 : 1/4	400	319	257	1/200	19
AET4450YHR	13.3	1/3	CSIR	3.5	831	3/8 : 1/4	498	338	298	1/250	28
AET4456YHR	14.5	1/2	CSIR	4.4	985	3/8 : 1/4	498	338	298	1/250	28
AET4460YHR	15.1	1/2	CSR	4.4	1023	3/8 : 1/4	498	338	298	1/250	28
CAJT4476YHR	21.8	5/8	CSIR	5.2	1219	1/2 : 3/8	495	430	340	1/300	37
CAJT4492YHR	26	3/4	CSIR	5.4	1566	1/2 : 3/8	610	510	445	1/350	42
CAJT4511YHR	32.7	1	CSR	5.7	2061	5/8 : 3/8	610	510	445	1/350	40
TAJT4511YHR	32.7	1	3ø	2.2							
FHT4518YHR	53.2	1 1/2	CSR	7.2	3050	5/8 : 3/8	618	1002	469	2/350	80
TFHT4518YHR	53.2	1 1/2	3ø	3.5							
FHT4525YHR	74.3	2	CSR	9.1	4000	5/8 : 3/8	618	1002	469	2/350	80
TFHT4525YHR	74.3	2	3ø	3.7							
TAGT4528YHR	90.2	2 1/2	3ø	4.2	4073	7/8 : 3/8	650	1080	565	2/400	87
TAGT4534YHR	100.7	2 3/4	3ø	5.2	5115	7/8 : 3/8	650	1080	565	2/400	98
TAGT4537YHR	112.5	3	3ø	5.5	5586	7/8 : 3/8	650	1080	565	2/400	98
TAGT4543YHR	124.5	3 1/2	3ø	5.9	6249	7/8 : 3/8	650	1080	565	2/400	104



Wholesale-Consulting-Engineering

For more information, please call Refrigeration Distributors (02) 9743 7911
1/10 Ferngrove Place, Chester Hill NSW 2162
www.rdl.com.au

