



Maneurop Compressors

Medium Temperature

Model	Displ. (cc)	HP	Refrigeration Capacity (Watts)		
			R404a @-5°C	R22 @-5°C	R22 @+7.2°C
MTZ18-5	30.23	1 1/2	2540	2210	4314
MTZ18-4					
MTZ22-5	38.12	1 3/4	3450	3200	5896
MTZ22-4					
MTZ28-5	48.06	2	4500	4700	7972
MTZ28-4					
MTZ32-5	53.9	2 1/2	5170	5000	8724
MTZ32-4					
MTZ36-5	60.47	3	6040	6001	9999
MTZ36-4					
MTZ40-4	67.89	3 1/2	6850	6610	11139
MTZ45-4	76.22	3 3/4	7040	6660	11788
MTZ50-4	85.64	4	8150	7700	13435
MTZ56-4	96.13	4 1/2	8830	8850	14958
MTZ64-4	107.7	5 1/2	10450	10004	17155
MTZ72-4	120.9	6	11630	11300	19464
MTZ80-4	135.7	6 1/2	13540	12710	22055
MTZ100-4	171.2	8 1/2	15970	14330	25530
MTZ125-4	215.4	10	20380	19180	33218
MTZ144-4	241.8	12	23810	21640	37610
MTZ160-4	271.5	13 1/2	26200	24091	41780

50°C condensing temperature, 11K superheat, 8.3K Subcooling

MTZ XX-4: 3 phase - 400V

MTZ XX-5: 1 phase - 240V

R404a Low Temperature

Model	Displ. (cc)	HP	Capacity @-25°C (Watts)
NTZ48-5	48	2.5	1138
NTZ48-4			
NTZ68-5	68	3.5	1849
NTZ68-4			
NTZ96-4	96	5	3069
NTZ108-4	108	5.5	3289
NTZ136-4	136	7	4533
NTZ215-4	215	10	6530
NTZ271-4	271	13	7831

50°C condensing temperature, 11K superheat, 8.3K Subcooling

MTZ XX-4: 3 phase - 400V

MTZ XX-5: 1 phase - 240V

For more information, please call Refrigeration Distributors (02) 9743 7911

1/10 Ferngrove Place, Chester Hill NSW 2162

www.rdl.com.au



Wholesale-Consulting-Engineering

